EN60598 IK08 IP66 RoHS **LUN 1036 P6 730 R3 400 9006 0 * xx**

LUNIA

With a modern, timeless design LUNIA LED street light can easily be recognized by its individual, unostentatious shape. LUNIA combines highest technical demands and design in a single high-quality product.

Technical Data

Material	AlSi12-LM6
Housing color	RAL 9006
Glass cover	safety flat glass
Application / optics	narrow street / R3
LED lifetime	L80 > 100 000 h
SDCM	MacAdam 5
Mounting	Post top
Bracket diameter	60 mm
Tilting angle	±3°, adjustable
Weight	9,8 kg
Windage Area	0,079 m²
Temperature	-40°C to +50°C
Nominal voltage	220 - 240 VAC 50/60 Hz

Light file

LUN 1036 730 R3 400



more on the Internet

Specific data

Color temperature	3000 K
CRI	75
System light output	4780 lm
Power consumption	45,3 W
Ø 0 h - 100 000 h	47,5 W
> 100 000 h	49,7 W
System efficacy	106 lm/W
LED current	400 mA
cos Phi	0,97
Driver typ	TD75
Surge protection	10 kV / 6 kV [1]
Inrush current	37 A

* Functions (more on request)
21 on / off
25 Luna Dimmer
33 Dali integrated

all values at Ta =25°C

[1] *Common Mode / Differential Mode*



Dimensional Drawing in mm

SWARCO FUTURIT Verkehrssignalsysteme GesmbH
Vertrieb I Technik I Verwaltung, Mühlgasse 86, A-2380 Perchtoldsdorf, Austria, T. +43-1-8957924, F. +43-1-8942148
Produktion I Einkauf, Manfred-Swarovski-Straße 1, A-7343 Neutal, Austria, T. +43-2618-20025-0, F. +43-2618-20025-50
E: office.futurit@swarco.com, www.swarco.com

Version 7.190219

Changes, literal errors reserved